



KEIM Concretal-W

DECLARATION OF PERFORMANCE

Number of the declaration of performance and unique identification of the product-type
02 0004.1

Intended use

Surface protection product – Coating

Regulation of moisture balance (2.2)

Increase of electrical resistance (8.2)

Manufacturer

KEIMFARBEN GMBH, Keimstraße 16, D-86420 Diedorf

System of AVCP

System 2+

(for intended use in buildings and engineering structures)

System 3

(for intended purposes subject to reaction to fire regulations)

Harmonised standard

EN 1504-2:2004

Notified body

Materialprüfungs- und Forschungsanstalt, MPA Karlsruhe, identification number 0754

Fire behaviour: Technische Universität München Holzforschung München, identification number 0797

Declared performance

Essential characteristics	Performance	System of AVCP
Water vapor permeability	Class I	System 2+
Capillary water absorption	$w < 0,1 \text{ kg/m}^2\text{h}^{0,5}$	
Coating adhesion strength in pulloff test	$\geq 1,0 (0,7)^{1)} \text{ N/mm}^2$	
Fire behaviour	Class A2-s1, d0	System 3
Hazardous substances	NPD	System 2+

¹⁾ The value in brackets is the smallest, permissible value per reading.

Keimstraße 16 / 86420 Diedorf
Tel. +49 (0)821 4802-0
Fax +49(0)821 4802-210

Frederik-Ipsen-Straße 6 / 15926 Luckau
Tel. +49(0) 35456 676-0
Fax +49(0) 35456 676-38

www.keimfarben.de
info@keimfarben.de

Deutsche Bank München
IBAN DE37 7007 0010 0188 1580 00
BIC DEUTDE33

Stadtparkasse Augsburg
IBAN DE48 7205 0000 0000 3621 03
BIC AUGSDE33

Registergericht Augsburg HRB 27263
Geschäftsführer: Rüdiger Lugert



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Manager of quality assurance and color metrics:

Diedorf, 01.12.2017



p.p. Peter Jaser

Appendix
Material safety data sheet