

SUSTAINABILITY DATA SHEET

KEIM AQUAROYAL®-MINERALPUTZ

1. PRODUCT DESCPRIPTION

KEIM AquaROYAL-Mineralputz is a mineral, hydroactive premium plaster used as a finish plaster within the AquaROYAL render and coating system. KEIM AquaROYAL-Mineralputz is a factory-produced dry mortar GP according to DIN EN 998-1. For a detailed product description, as well as processing information, please refer to the Technical Data Sheet on www.keim.com.

2. INGREDIENTS

| Declaration of ingredients (according to VdL directive 01) (VdL: German Paint and Printing Ink Association) | White cement, white hydrated lime, polymer, inorganic coloured pigments (depending on shade), mineral fillers, fibres, hydrophobing agent, thickener, air entraining agent. |
|--|---|
| Declaration of ingredients (according to natureplus) | Not certified |
| Organic content (according to DIN 18363 section 2.4.1) | Not applicable |
| Solvent content (according to directive 2004/42/EC) | Not applicable |
| Plasticiser content (according to VdL directive 01) (VdL: German Paint and Printing Ink Association) | Not included (no recipe component) |
| Aromatic hydrocarbons | Not included (no recipe component) |
| Plasticiser content (according to VdL directive 01) (VdL: German Paint and Printing Ink Association) | Not included (no recipe component) |
| Hazardous ingredients (according to CLP regulation) | Refer to section 3 of safety data seet (link under section: Further documents) |
| Active ingredients for coating protection (film preservative, product type 7 as per BPR) | Not included (no recipe component) |
| Active ingredients for storage protection (film preservative, product type 6 as per BPR) | Not included (no recipe component) |
| Lead, cadmium, chromium VI, arsenic, mercury | Not included (no recipe component) |

| CMR substances of categories 1A and 1B (according to CLP regulation) | d Not included (no recipe component) |
|--|--|
| PBT and vPvB substances (according to REACH regulation) | Not included (no recipe component, see section 2 of Safety Data Sheet) |
| Ozone-depleting substances (according to regulation (EC) Nr. 1005/20 | Not included (no recipe component) |
| Formaldehyde | Not included (no recipe component) |
| Per- and polyfluorinated alkyl compounds (PFAS) (according to REACH regulation) | Not included (no recipe component) |
| Halogenated organic compounds | Refer to section 12 of safefty data seet (link under section: Further documents) |
| Compliance with the limitation of emissions of the titanium dioxide industry (according to directive 92/112/EEC or directive 2010/75/EU) | Does not contain titanium dioxide. |
| QNG-requirements (according to QNG version 1.3 in Attached Document 313) | Not classified |

3. TEST REPORTS / EXPERT REPORTS / CERTIFICATIONS / LOGOS

| Test reports | On demand |
|--|--------------|
| Export reports | On demand |
| Product code / GISCODE (according to directive 2004/42/EC) | ZP 1 |
| MAL code | Not relevant |
| Certification / Logos | |



4. INFORMATION FOR BUILDING CERTIFICATION AS PER DGNB

| Product group (ENV 1.2) | Not relevant |
|---|--|
| Solvent content (according to directive 2004/42/EC) | Not applicable |
| Dilutability with water (according to directive 2004/42/EC) | Yes |
| Product-specific life cycle assessment values (ENV 1.1 and ENV 2.1) | Not specified |
| Quality level (ENV 1.2) | Not relevant |
| Product-specific life cycle (ECO 1.1) | 30 years (according to BNB: National rating system for sustainable building) |
| Safety and risks of failure (SOC 1.7) | No negative influence, since no halogenes contained |
| Cleaning instruction (PRO 1.5, PRO 2.2) | Refer to technical data sheet (link under section: Further documents) |

5. ANGABEN ZUR EIGNUNG NACH LEED V4.1

| Product group (EQ4.2) | Flat Topcoat |
|--|--|
| VOC (as per SCAQMD Rule 1113, Architectural Coatings, rules in effect on February 5, 2016) | Not relevant |
| VOC limit met | Not relevant |
| Recycling rate (from post-consumer sources) (MR4) | KEIM AquaROYAL-Mineralputz can achieve the service life of the building components. KEIM AquaROYAL-Mineralputz does not have a real after-use phase. The final disposal is carried out in conjunction with the building components via building rubble. If it is pure building rubble, recycling takes place in accordance with national regulations. Normally, building rubble is crushed and returned to the economic cycle as a substitute for fillers (road construction, concrete). |
| Recycling rate (from production-relevant sources) (MR4) | 0 % |
| Fast renewable raw materials (MR 6) | 0 % |

| Regional materials (MR 5) | No information |
|------------------------------|---|
| Production site (MR 5) | KEIMFARBEN GMBH, Keimstraße 16, D-86420 Diedorf, Tel. +49 821 4802-0 |

6. MANAGEMENT SYSTEMS AND CORPORATE CERTIFICATIONS

| Quality and environmental | |
|---------------------------|--|
| management | |

The manufacturing/marketing company is certified according to DIN EN ISO 9001 and DIN EN ISO 14001. The company performs a regular energy audit according to DIN EN 16247-1.

7. SAFETY INSTRUCTIONS

See materials safety data sheet

(link under section: Further documents)

8. FURTHER DOCUMENTS

Further documents can be found under https://www.keim.com/en-de/products/etic-systems/aquaroyal/aquaroyal-mw/.

The idea of sustainability defines and guides our joint entrepreneurial activities. Our belief in the added value of mineral building products takes this premise into account. The character of our company is shaped by the spirit of its founder. For more than 140 years, we have been committed to A. W. Keim's guiding principle of looking carefully to the future and subsequent generations. To this day, this premise carries our entrepreneurial activities far beyond the innovative use of natural raw materials - by creating regional jobs, valuing our employees and handling our limited resources with care. Sustainable building and renovation are therefore a very decisive contribution to a healthy living situation, quality of life and a better future. This document is therefore intended to help you to assess the sustainability of our products.

The information is based on the requirements of the product data sheet of VDL Guideline 11 (4th revision). Further details are additional information.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.